

## Quad 2-Input AND Gate

### DESCRIPTION

The 74HC08 is identical in pinout to the LS/ALS08. The device inputs are compatible with standard CMOS outputs; with pullup resistors, they are compatible with LS/ALSTTL outputs.

### FEATURES

- Outputs Directly Interface to CMOS, NMOS, and TTL
- Operating Voltage Range: 2.0 to 6.0 V
- Low Input Current: 1.0  $\mu$ A
- High Noise Immunity Characteristic of CMOS Devices
- TA = -40° to 125° C for all packages

### ORDERING INFORMATION

| Part Number | Package  | Packing | Temperature(TA) | Package Qty |
|-------------|----------|---------|-----------------|-------------|
| 74HC08D     | SOIC-14  | Reel    | -40°C ~ 125°C   | 2500        |
| 74HC08P     | TSSOP-14 | Reel    | -40°C ~ 125°C   | 2500        |


### PIN ASSIGNMENT

|     |     |    |                 |
|-----|-----|----|-----------------|
| A1  | 1 ● | 14 | V <sub>CC</sub> |
| B1  | 2   | 13 | B4              |
| Y1  | 3   | 12 | A4              |
| A2  | 4   | 11 | Y4              |
| B2  | 5   | 10 | B3              |
| Y2  | 6   | 9  | A3              |
| GND | 7   | 8  | Y3              |

### FUNCTION TABLE

| Inputs |   | Output |
|--------|---|--------|
| A      | B | Y      |
| L      | L | L      |
| L      | H | L      |
| H      | L | L      |
| H      | H | H      |

### LOGIC DIAGRAM



PIN 14 = V<sub>CC</sub> PIN 7 = GND

**MAXIMUM RATINGS**

| Symbol    | Parameter  | Value                  | Unit |
|-----------|--|------------------------|------|
| $V_{CC}$  | DC Supply Voltage (Referenced to GND)  | -0.5 to +7.0           | V    |
| $V_{IN}$  | DC Input Voltage (Referenced to GND)   | -1.5 to $V_{CC} + 1.5$ | V    |
| $V_{OUT}$ | DC Output Voltage (Referenced to GND)  | -0.5 to $V_{CC} + 0.5$ | V    |
| $I_{IN}$  | DC Input Current, per Pin  | $\pm 20$               | mA   |
| $I_{OUT}$ | DC Output Current, per Pin   | $\pm 25$               | mA   |
| $I_{CC}$  | DC Supply Current, $V_{CC}$ and GND Pins   | $\pm 50$               | mA   |
| $P_D$     | Power Dissipation in Still Air, Plastic DIP**<br>SOIC Package**                  | 750<br>500             | mW   |
| Tstg      | Storage Temperature  | -55 to +150            | °C   |
| $T_L$     | Lead Temperature, 1 mm from Case for 10 Seconds<br>(Plastic DIP or SOIC Package) | 260                    | °C   |

Maximum Ratings are those values beyond which damage to the device may occur.

**RECOMMENDED OPERATING CONDITIONS**

| Symbol            | Parameter  | Min | Max      | Unit |
|-------------------|--|-----|----------|------|
| $V_{CC}$          | DC Supply Voltage (Referenced to GND)                | 2.0 | 6.0      | V    |
| $V_{IN}, V_{OUT}$ | DC Input Voltage, Output Voltage (Referenced to GND) | 0   | $V_{CC}$ | V    |
| $T_A$             | Operating Temperature, All Package Types             | -40 | +125     | °C   |
| $t_r, t_f$        | Input Rise and Fall Time (Figure 1)                  |     |          | ns   |
|                   | $V_{CC} = 2.0\text{ V}$                              | 0   | 1000     |      |
|                   | $V_{CC} = 4.5\text{ V}$                              | 0   | 500      |      |
|                   | $V_{CC} = 6.0\text{ V}$                              | 0   | 400      |      |

This device contains protection circuitry to guard against damage due to high static voltages or electric fields. However, precautions must be taken to avoid applications of any voltage higher than maximum rated voltages to this high-impedance circuit. For proper operation,  $V_{IN}$  and  $V_{OUT}$  should be constrained to the range  $GND \leq (V_{IN} \text{ or } V_{OUT}) \leq V_{CC}$ .

Unused inputs must always be tied to an appropriate logic voltage level (e.g., either GND or  $V_{CC}$ ). Unused outputs must be left open.



**DC ELECTRICAL CHARACTERISTICS** (Voltages Referenced to GND)

| Symbol          | Parameter                              | Test Conditions  | V <sub>CC</sub><br>V | Guaranteed Limit     |           |            | Unit |
|-----------------|--|--|----------------------|----------------------|-----------|------------|------|
|                 |  |  |                      | 25 °C<br>to<br>-55°C | ≤85<br>°C | ≤125<br>°C |      |
| V <sub>IH</sub> | Minimum High-Level Input Voltage       | V <sub>OUT</sub> =0.1 V or V <sub>CC</sub> -0.1 V<br>  I <sub>OUT</sub>   ≤ 20 μA                                      | 2.0                  | 1.5                  | 1.5       | 1.5        | V    |
|                 |  |  | 4.5                  | 3.15                 | 3.15      | 3.15       |      |
|                 |  |  | 6.0                  | 4.2                  | 4.2       | 4.2        |      |
| V <sub>IL</sub> | Maximum Low-Level Input Voltage        | V <sub>OUT</sub> =0.1 V or V <sub>CC</sub> -0.1 V<br>  I <sub>OUT</sub>   ≤ 20 μA                                      | 2.0                  | 0.5                  | 0.5       | 0.5        | V    |
|                 |  |  | 4.5                  | 1.35                 | 1.35      | 1.35       |      |
|                 |  |  | 6.0                  | 1.8                  | 1.8       | 1.8        |      |
| V <sub>OH</sub> | Minimum High-Level Output Voltage      | V <sub>IN</sub> =V <sub>IH</sub> or V <sub>IL</sub><br>  I <sub>OUT</sub>   ≤ 20 μA                                    | 2.0                  | 1.9                  | 1.9       | 1.9        | V    |
|                 |  |  | 4.5                  | 4.4                  | 4.4       | 4.4        |      |
|                 |  | 6.0  | 5.9                  | 5.9                  | 5.9       |            |      |
|                 |  | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>  I <sub>OUT</sub>   ≤ 4.0 mA<br>  I <sub>OUT</sub>   ≤ 5.2 mA | 4.5                  | 3.98                 | 3.84      | 3.7        |      |
| 6.0             | 5.48                                   | 5.34   | 5.2                  |                      |           |            |      |
| V <sub>OL</sub> | Maximum Low-Level Output Voltage       | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>  I <sub>OUT</sub>   ≤ 20 μA                                   | 2.0                  | 0.1                  | 0.1       | 0.1        | V    |
|                 |  |  | 4.5                  | 0.1                  | 0.1       | 0.1        |      |
|                 |  | 6.0  | 0.1                  | 0.1                  | 0.1       |            |      |
|                 |  | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub><br>  I <sub>OUT</sub>   ≤ 4.0 mA<br>  I <sub>OUT</sub>   ≤ 5.2 mA | 4.5                  | 0.26                 | 0.33      | 0.4        |      |
| 6.0             | 0.26                                   | 0.33   | 0.4                  |                      |           |            |      |
| I <sub>IN</sub> | Maximum Input Leakage Current          | V <sub>IN</sub> =V <sub>CC</sub> or GND  | 6.0                  | ±0.1                 | ±1.0      | ±1.0       | μA   |
| I <sub>CC</sub> | Quiescent Supply Current (per Package) | V <sub>IN</sub> =V <sub>CC</sub> or GND<br>I <sub>OUT</sub> =0μA   | 6.0                  | 1.0                  | 10        | 40         | μA   |


**AC ELECTRICAL CHARACTERISTICS** ( $C_L=50\text{pF}$ , Input  $t_r=t_f=6.0\text{ ns}$ )

| Symbol                | Parameter   | $V_{CC}$<br>V | Guaranteed Limit     |       |        | Unit |
|-----------------------|---|---------------|----------------------|-------|--------|------|
|                       |   |               | 25 °C<br>to<br>-55°C | ≤85°C | ≤125°C |      |
| $t_{PLH}$ , $t_{PHL}$ | Maximum Propagation Delay, Input A or B to Output Y (Figures 1 and 2) | 2.0           | 75                   | 95    | 110    | ns   |
|                       |   | 4.5           | 15                   | 19    | 22     |      |
|                       |   | 6.0           | 13                   | 16    | 19     |      |
| $t_{TLH}$ , $t_{THL}$ | Maximum Output Transition Time, Any Output (Figures 1 and 2)          | 2.0           | 75                   | 95    | 110    | ns   |
|                       |   | 4.5           | 15                   | 19    | 22     |      |
|                       |   | 6.0           | 13                   | 16    | 19     |      |
| $C_{IN}$              | Maximum Input Capacitance   | -             | 10                   | 10    | 10     | pF   |

|          |  |   |  |  |    |
|----------|--|---|--|--|----|
| $C_{PD}$ | Power Dissipation Capacitance (Per Gate)   | $T_A=25^\circ\text{C}, V_{CC}=5.0\text{ V}$ |  |  | pF |
|          | Used to determine the no-load dynamic power consumption:<br>$P_D=C_{PD}V_{CC}^2f+I_{CC}V_{CC}$ | 20  |  |  |    |



**Figure 1 Switching Waveforms.**


\*Includes all probe and jig capacitance.

**Figure 2. Test Circuit**
**EXPANDED LOGIC DIAGRAM**  
 (1/4 of the Device)


## Package diagram

SOIC14: plastic small outline package; 14 leads; body width 3.9 mm



**TSSOP14: plastic thin shrink small outline package; 14 leads; body width 4.4 mm**
